

128GB Computer memory DDR4 for Cisco UCS B200 M6 RDIMM 3DS





Your benefits ✓ verified quality memory ✓ 5 years warranty Warranty details see last page ✓ 100% compatible ✓ free support on our hotline ✓ fast delivery

PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



Memory Specification



Memory size	128GB		
Memory technology	DDR4		
ECC support	yes		
JEDEC Norm	PC4-25600-R		
DRAM Organization	3DS 2H 8Gx4		
Rank	4Rx4 (2S2Rx4)		
Type RDIMM (ECC Registered) 3DS			
Number of pins	288 Pin DIMM		
Memory data transfer rate	3200MHz @ CL22		
Voltage	1,2 Volt		
Speciality	3DS		
Board dimensions	133,35 x 31,25 (LxB mm)		
Operating temperature	0° C - 85° C		
Storage temperature	-40° C - +95° C		
RoHS compliant	yes		
SKU	SP538635		
EAN	4069169000562		

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



System Specifications

The memory is 100% compatible with this sytem:

Cisco
Server
UCS
B200 Serie
UCS B200 M6
8TB
32

^{*}The specifications for the maximum memory upgrade may differ from those of the manufacturer Cisco. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

Information on memory allocation

Information on memory configuration

The following technical specifications should be considered in advance:

- The system supports RDIMM and RDIMM 3DS (Registered DIMM) or LRDIMM and LRDIMM 3DS (Load Reduced DIMM) memory modules. Large memory capacities can be realised with LRDIMM 3DS modules.
- RDIMM and RDIMM 3DS memory modules cannot be operated together with LRDIMM and LRDIMM 3DS main memories.
- If a memory expansion is to be made with the already existing RAM memories, it must be checked which basic memory technology (RDIMM / LRDIMM) is available.
- When using a multiprocessor system, the memory slots should always be configured identically for each CPU.
- Memory slots without a processor may not be used.
- If memory modules are provided with higher speeds than specified by the system, the memory speed is automatically adjusted to the system specifications.
- The CPU supports 6 DIMMs per memory channel.

Maximum memory speed of possible CPUs

Xeon CPUs of the 2nd generation are offered in Bronze, Silver, Gold or Platinum. The different processor series also support different maximum memory speeds:

Xeon	CPU-series	max. Speed MHz	max. memory capacity je CPU	
Bronze	3200	2133	1 TB	
Silver	4200	2400	1 TB	
Gold	5200	2666	1 TB, 2 TB, 4,5 TB	
Gold	6200	2666	1 TB, 2 TB, 4,5 TB	
Platinum	8200	2933	1 TB, 2 TB, 4,5 TB	
Platinum	9200	2933	1,5 TB	



Information on memory installation

- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
 - Do not touch the gold pins of the memory module
 - Only touch the sides of the memory module
 - Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.



Further memory options for Cisco UCS B200 M6

8GB SP538631 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 16GB SP538632 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 32GB SP538633 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP538634 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP538629 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP538635 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP538630 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 256GB SP538636 DDR4 RDIMM (ECC 288 Pin DIMM PHS-memory®	Size	SKU	Technology	Туре	Number of pins	Brand	Reference no.
Registered) 32GB SP538633 DDR4 RDIMM (ECC Registered) 64GB SP538634 DDR4 RDIMM (ECC Registered) 64GB SP538629 DDR4 LRDIMM (ECC LR DIMM) 128GB SP538635 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory®	8GB	SP538631	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered) 64GB SP538634 DDR4 RDIMM (ECC Registered) 64GB SP538629 DDR4 LRDIMM (ECC LR DIMM) 128GB SP538635 DDR4 RDIMM (ECC Registered) 3DS 128GB SP538630 DDR4 LRDIMM (ECC LR DIMM) 128GB SP538630 DDR4 LRDIMM (ECC Registered) 3DS 128GB SP538630 DDR4 LRDIMM (ECC LR DIMM) PHS-memory® PHS-	16GB	SP538632	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered) 64GB SP538629 DDR4 LRDIMM (ECC LR DIMM) PHS-memory® 128GB SP538635 DDR4 RDIMM (ECC Registered) 3DS PHS-memory® 128GB SP538630 DDR4 LRDIMM (ECC LR DIMM) PHS-memory® 128GB SP538630 DDR4 LRDIMM (ECC LR DIMM)	32GB	SP538633	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM) 128GB SP538635 DDR4 RDIMM (ECC Registered) 3DS 128GB SP538630 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory® LR DIMM) PHS-memory®	64GB	SP538634	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered) 3DS 128GB SP538630 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory® LR DIMM)	64GB	SP538629	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM)	128GB	SP538635	DDR4	•	288 Pin DIMM	PHS-memory®	
256GB SP538636 DDR4 RDIMM (ECC 288 Pin DIMM PHS-memory®	128GB	SP538630	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered) 3DS	256GB	SP538636	DDR4	•	288 Pin DIMM	PHS-memory®	

PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.

For more information on warranty and service please visit https://www.phs-memory.com/-W5Y



Contact Information

PHS-electronic gmbh
- www.phs-memory.com Karl-Götz-Str. 5
97424 Schweinfurt
Germany

Phone: +49 9721 784678 E-Mail: info@phs-memory.com Web: www.phs-memory.com

All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at https://www.phs-memory.com