

64GB Computer memory DDR4 for Dell PowerEdge T630 RDIMM



PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



Memory Specification



Memory size	64GB		
Memory technology	DDR4		
ECC support	yes		
JEDEC Norm	PC4-2400T-R		
DRAM Organization	4Gx4		
Rank	2Rx4		
Туре	RDIMM (ECC Registered)		
Number of pins	288 Pin DIMM		
Memory data transfer rate	2400MHz @ CL17		
Voltage	1,2 Volt		
Speciality	-, DDP		
Board dimensions	133,35 x 31,25 (LxB mm)		
Operating temperature	0° C - 85° C		
Storage temperature	-40° C - +95° C		
RoHS compliant	yes		
SKU	SP462485		
EAN	4067488259852		

overRAMing maximize your RAM



Most systems - including the Dell PowerEdge T630 - can be upgraded with more memory than originally specified by the device manufacturer.

Therefore, our memory specialists continuously analyze new memory solutions in selected systems. Due to improved manufacturing technologies, new memories with higher performance and capacity will be tested for stability and functionality. Then the new memory solutions are released for the respective systems.

The respective systems. Use the benefits of larger computer memory capacity with the PHSmemory® overRAMing memory solutions.

https://www.phs-memory.com/-BOR

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



System Specifications

The memory is 100% compatible with this sytem:

System manufacturer	Dell		
Device type	Server		
Device family	PowerEdge		
Device series	T600 Serie		
Device name	PowerEdge T630		
Maximum memory*	3TB / 768GB according to manufacturer		
Number of memory sockets	24		

* The specifications for the maximum memory upgrade may differ from those of the manufacturer Dell. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

Memory modules with our overRAMing-symbol are approved by us for maximum memory expansion.

Information on memory allocation

Information on memory configuration

The following technical specifications should be considered in advance:

- The system supports RDIMM and RDIMM 3DS (Registered DIMM) or LRDIMM and LRDIMM 3DS (Load Reduced DIMM) memory modules. Large memory capacities can be realised with LRDIMM 3DS modules.
- RDIMM and RDIMM 3DS memory modules cannot be operated together with LRDIMM and LRDIMM 3DS main memories.
- If a memory expansion is to be made with the already existing RAM memories, it must be checked which basic memory technology (RDIMM / LRDIMM) is available.
- Memory slots without a processor may not be used.
- A higher memory clock of the memory module automatically adapts to the memory clock specified by the system. This can be the case especially with larger capacities.

Information on memory installation

- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
- Do not touch the gold pins of the memory module
- Only touch the sides of the memory module
- Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.



Further memory options for Dell PowerEdge T630

8GBSP146487DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory@A791048716GBSP146486DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory@ Registered)A7910488, SNP1R8CRC/16 G32GBSP160385DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory@ Registered)SNPTN78YC/32 G, A9781929, 370-ADNF, SNP75X1VC/32 G, AA799087, AA579531, SNP 8WKDYC/32G64GBSP462485DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory@64GBSP146490DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory@128GBSP462483DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory@128GBSP462483DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory@	Size	SKU	Technology	Туре	Number of pins	Brand	Reference no.
Registered)SNP1R8CRC/16 G32GBSP160385DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory® SNPTSX1VC/32 G, A9781929, 370-ADNF, SNP75X1VC/32G64GBSP462485DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory® sNP75X1VC/32G64GBSP462485DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory® sWKDYC/32G64GBSP146490DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®128GBSP462484DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®128GBSP462483DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®	8GB	SP146487	DDR4	•	288 Pin DIMM	PHS-memory®	A7910487
Registered)Registered)G, A9781929, 370-ADNF, SNP75X1VC/32 G, AA799087, AA579531, SNP 8WKDYC/32G64GBSP462485DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory®64GBSP146490DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®128GBSP462484DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®128GBSP462483DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®	16GB	SP146486	DDR4	``	288 Pin DIMM	PHS-memory®	SNP1R8CRC/16
Registered)64GBSP146490DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®128GBSP462484DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®128GBSP462483DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®	32GB	SP160385	DDR4		288 Pin DIMM	PHS-memory®	G, A9781929, 370-ADNF, SNP75X1VC/32 G, AA799087, AA579531, SNP
LR DIMM) LR DIMM) 128GB SP462484 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP462483 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory®	64GB	SP462485	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM) 128GB SP462483 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory®	64GB	SP146490	DDR4	•	288 Pin DIMM	PHS-memory®	
	128GB	SP462484	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM) 3DS	128GB	SP462483	DDR4	LRDIMM (ECC LR DIMM) 3DS	288 Pin DIMM	PHS-memory®	

PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.

For more information on warranty and service please visit https://www.phs-memory.com/-W5Y



Contact Information

PHS-electronic gmbh - www.phs-memory.com -Karl-Götz-Str. 5 97424 Schweinfurt Germany Phone: +49 9721 784678 E-Mail: info@phs-memory.com Web: www.phs-memory.com

All information without guarantee. Technical changes and errors excepted. You can find current price information in our online



shop at https://www.phs-memory.com