

128GB SSD350R - Industrial SSD - 2.5 inch SATA III SSD - 3D TLC - SP128GISSD355RV0



Preis auf Anfrage

<https://www.phs-memory.com>

Version: 05.09.2025 23:51

Your benefits

- ✓ verified quality
- ✓ many years of IT competence
- ✓ high availability
- ✓ free support on our hotline
- ✓ fast delivery

100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspections include checks of the components in order to exclude possible errors already in the incoming goods department (Controlled BOM).
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel

Product information

General

Interface	SATA III/6.0Gbps
Flash Technology	TLC
Capacity	128GB
Form Factor	2.5 inch
Dimensions	100.4 x 69.9 x 6.8 mm
External DRAM Buffer	Yes
Manufacturer Part No.	SP128GISSD355RV0

Performance

Seq. Performance Read (max.)	560 MB/s
Seq. Performance Write (max.)	520 MB/s
Random 4K Read (IOPS max.)	95,000
Random 4K Write (IOPS max.)	91,000
MTBF @ 25 °C	>3,000,000 hrs
P/E Cycle	3,000
TBW	343 TB

Operating Environment

Operating Temperature	-20°C~75°C
Storage Temperature	-55°C~95°C
Operating Humidity	10%~95% (30°C Max. Wet Bulb Temp)
Vibration	20G, 10~2000Hz
Drop	75cm
Shock	1,500G@0.5ms

Power Consumption

Power Requirement	DC 5.0V
Power Operation (max.)	700 mA
Power Idle / Standby	110 mA

Key Features

Power Failure Protection (PFP)	Yes
Advanced Power Shield	Yes
End-to-End Data Protection	Optional
TCG Opal 2.0	Optional
AES-256	Optional
Thermal Throttling	Yes
DEVSLP	Yes
S.M.A.R.T	Yes

EAN	4713436140000
------------	---------------

manufacturer	Silicon Power
---------------------	---------------

Other possible options

Product	SKU	Brand	Reference no.
128GB SSD350R - Industrial SSD - 2,5 Zoll SATA III SSD - 3D TLC - SP128GISSD355RV0	SP596259	Silicon Power	SP128GISSD355RV0
512GB SSD350R - Industrial SSD - 2,5 Zoll SATA III SSD - 3D TLC - SP512GISSD355RV0	SP596260	Silicon Power	SP512GISSD355RV0
960GB SSD350R - Industrial SSD - 2,5 Zoll SATA III SSD - 3D TLC - SP960GISSD355RV0	SP596261	Silicon Power	SP960GISSD355RV0
128GB SSD350R - Industrial SSD - 2,5 Zoll SATA III SSD - 3D TLC - Wide Temp - SP128GISSD355RW0	SP596262	Silicon Power	SP128GISSD355RW0
256GB SSD350R - Industrial SSD - 2,5 Zoll SATA III SSD - 3D TLC - Wide Temp - SP256GISSD355RW0	SP596263	Silicon Power	SP256GISSD355RW0
512GB SSD350R - Industrial SSD - 2,5 Zoll SATA III SSD - 3D TLC - Wide Temp - SP512GISSD355RW0	SP596264	Silicon Power	SP512GISSD355RW0
1TB SSD350R - Industrial SSD - 2,5 Zoll SATA III SSD - 3D TLC - Wide Temp - SP010TISSD355RW0	SP596265	Silicon Power	SP010TISSD355RW0
2TB SSD350R - Industrial SSD - 2,5 Zoll SATA III SSD - 3D TLC - Wide Temp - SP020TISSD355RW0	SP596266	Silicon Power	SP020TISSD355RW0

Contact Information

PHS-electronic gmbh
 - www.phs-memory.com -
 Karl-Götz-Str. 5
 97424 Schweinfurt
 Germany

Phone: +49 9721 784678
 E-Mail: info@phs-memory.com
 Web: www.phs-memory.com

All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at <https://www.phs-memory.com>