

## 256GB Computer memory DDR4 for Gigabyte R281-N40 (rev. 400) RDIMM 3DS





# Your benefits ✓ verified quality memory ✓ 5 years warranty Warranty details see last page ✓ 100% compatible ✓ free support on our hotline ✓ fast delivery

#### PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



#### Memory Specification



Memory size	256GB
Memory technology	DDR4
ECC support	yes
JEDEC Norm	PC4-25600-R
DRAM Organization	3DS 4H 16Gx4
Rank	8Rx4 (2S4Rx4)
Туре	RDIMM (ECC Registered) 3DS
Number of pins	288 Pin DIMM
Memory data transfer rate	3200MHz @ CL22
Voltage	1,2 Volt
Speciality	3DS
Board dimensions	133,35 x 31,25 (LxB mm)
Operating temperature	0° C - 85° C
Storage temperature	-40° C - +95° C
RoHS compliant	yes
SKU	SP472351
EAN	4067488358609

### overRAMing - maximize your RAM



Most systems - including the Gigabyte R281-N40 (rev. 400) - can be upgraded with more memory than originally specified by the device manufacturer.

Therefore, our memory specialists continuously analyze new memory solutions in selected systems. Due to improved manufacturing technologies, new memories with higher performance and capacity will be tested for stability and functionality.

Then the new memory solutions are released for the respective systems. Use the benefits of larger computer memory capacity with the PHSmemory® overRAMing memory solutions.

https://www.phs-memory.com/-BOR

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



#### System Specifications

The memory is 100% compatible with this sytem:

System manufacturer	Gigabyte
Device type	Server
Device family	Rack Server
Device series	R281 Serie
Device name	R281-N40 (rev. 400)
Maximum memory*	6TB / 3TB according to manufacturer
Number of memory sockets	24

<sup>\*</sup>The specifications for the maximum memory upgrade may differ from those of the manufacturer Gigabyte. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

Memory modules with our overRAMing-symbol are approved by us for maximum memory expansion.

#### Information on memory allocation

#### Information on memory configuration

The following technical specifications should be considered in advance:

- The system supports RDIMM and RDIMM 3DS (Registered DIMM) or LRDIMM and LRDIMM 3DS (Load Reduced DIMM) memory modules. Large memory capacities can be realised with LRDIMM 3DS modules.
- RDIMM and RDIMM 3DS memory modules cannot be operated together with LRDIMM and LRDIMM 3DS main memories.
- If a memory expansion is to be made with the already existing RAM memories, it must be checked which basic memory technology (RDIMM / LRDIMM) is available.
- When using a multiprocessor system, the memory slots should always be configured identically for each CPU.
- Memory slots without a processor may not be used.
- If memory modules are provided with higher speeds than specified by the system, the memory speed is automatically adjusted to the system specifications.
- The CPU supports 6 DIMMs per memory channel.

#### Maximum memory speed of possible CPUs

Xeon CPUs of the 2nd generation are offered in Bronze, Silver, Gold or Platinum. The different processor series also support different maximum memory speeds:

Xeon	CPU-series	max. Speed MHz	max. memory capacity je CPU	
Bronze	3200	2133	1 TB	
Silver	4200	2400	1 TB	
Gold	5200	2666	1 TB, 2 TB, 4,5 TB	
Gold	6200	2666	1 TB, 2 TB, 4,5 TB	
Platinum	8200	2933	1 TB, 2 TB, 4,5 TB	
Platinum	9200	2933	1,5 TB	



#### Information on memory installation

- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
  - Do not touch the gold pins of the memory module
  - Only touch the sides of the memory module
  - Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.



#### Further memory options for Gigabyte R281-N40 (rev. 400)

8GB         SP365523         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           16GB         SP365520         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           32GB         SP365521         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           64GB         SP365522         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           64GB         SP365519         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP472350         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP469590         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           128GB         SP365518         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           256GB         SP472351         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           256GB         SP469588         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®	Size	SKU	Technology	Туре	Number of pins	Brand	Reference no.
Registered)           32GB         SP365521         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           64GB         SP365522         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           64GB         SP365519         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP472350         DDR4         LRDIMM (ECC LR DIMM) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP469590         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP365518         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           256GB         SP472351         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP469588         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	8GB	SP365523	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered)           64GB         SP365522         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           64GB         SP365519         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP472350         DDR4         LRDIMM (ECC LR DIMM) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP469590         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP365518         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           256GB         SP472351         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP469588         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	16GB	SP365520	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered)           64GB         SP365519         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP472350         DDR4         LRDIMM (ECC LR DIMM) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP469590         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP365518         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           256GB         SP472351         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP469588         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	32GB	SP365521	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM)         128GB       SP472350       DDR4       LRDIMM (ECC LR DIMM) 3DS       288 Pin DIMM       PHS-memory®         128GB       SP469590       DDR4       RDIMM (ECC Registered) 3DS       288 Pin DIMM       PHS-memory®         128GB       SP365518       DDR4       LRDIMM (ECC LR DIMM)       288 Pin DIMM       PHS-memory®         256GB       SP472351       DDR4       RDIMM (ECC Registered) 3DS       288 Pin DIMM       PHS-memory®         256GB       SP469588       DDR4       LRDIMM (ECC 288 Pin DIMM       PHS-memory®	64GB	SP365522	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM) 3DS         128GB       SP469590       DDR4       RDIMM (ECC Registered) 3DS       288 Pin DIMM       PHS-memory®         128GB       SP365518       DDR4       LRDIMM (ECC LR DIMM)       288 Pin DIMM       PHS-memory®         256GB       SP472351       DDR4       RDIMM (ECC Registered) 3DS       288 Pin DIMM       PHS-memory®         256GB       SP469588       DDR4       LRDIMM (ECC 288 Pin DIMM       PHS-memory®	64GB	SP365519	DDR4	`	288 Pin DIMM	PHS-memory®	
Registered) 3DS           128GB         SP365518         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           256GB         SP472351         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP469588         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	128GB	SP472350	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM)           256GB         SP472351         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP469588         DDR4         LRDIMM (ECC 288 Pin DIMM PHS-memory®	128GB	SP469590	DDR4	,	288 Pin DIMM	PHS-memory®	
Registered) 3DS  256GB SP469588 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory®	128GB	SP365518	DDR4	•	288 Pin DIMM	PHS-memory®	
· ·	256GB	SP472351	DDR4	•	288 Pin DIMM	PHS-memory®	
LIV DIIVIIVI) DDS	256GB	SP469588	DDR4	LRDIMM (ECC LR DIMM) 3DS	288 Pin DIMM	PHS-memory®	

#### PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.

For more information on warranty and service please visit https://www.phs-memory.com/-W5Y



#### Contact Information

PHS-electronic gmbh
- www.phs-memory.com Karl-Götz-Str. 5
97424 Schweinfurt
Germany

Phone: +49 9721 784678 E-Mail: info@phs-memory.com Web: www.phs-memory.com

#### Product Datasheet | SP472351 256GB Computer memory for R281-N40 (rev. 400)



All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at https://www.phs-memory.com