

# 128GB Computer memory DDR4 for Supermicro SuperServer SYS-220HE-TNRD LRDIMM 3DS





# Your benefits ✓ verified quality memory ✓ 5 years warranty Warranty details see last page ✓ 100% compatible ✓ free support on our hotline ✓ fast delivery

## PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



# Memory Specification



Memory size	128GB
Memory technology	DDR4
ECC support	yes
JEDEC Norm	PC4-25600-L
DRAM Organization	3DS 4H 8Gx4
Rank	8Rx4 (2S4Rx4)
Туре	LRDIMM (ECC LR DIMM) 3DS
Number of pins	288 Pin DIMM
Memory data transfer rate	3200MHz @ CL22
Voltage	1,2 Volt
Speciality	3DS
Board dimensions	133,35 x 31,25 (LxB mm)
Operating temperature	0° C - 85° C
Storage temperature	-40° C - +95° C
RoHS compliant	yes
CIVII	SP473538
SKU	
EAN	4067488370496

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



### System Specifications

The memory is 100% compatible with this sytem:

System manufacturer	Supermicro		
Device type	Server		
Device family	SuperServer		
Device series	SYS-220 Serie		
Device name	SuperServer SYS-220HE-TNRD		
Maximum memory*	8TB		
Number of memory sockets	32		

<sup>\*</sup> The specifications for the maximum memory upgrade may differ from those of the manufacturer Supermicro. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

### Information on memory allocation

### Information on memory configuration

The following technical specifications should be considered in advance:

- The system supports RDIMM and RDIMM 3DS (Registered DIMM) or LRDIMM and LRDIMM 3DS (Load Reduced DIMM) memory modules. Large memory capacities can be realised with LRDIMM 3DS modules.
- RDIMM and RDIMM 3DS memory modules cannot be operated together with LRDIMM and LRDIMM 3DS main memories.
- If a memory expansion is to be made with the already existing RAM memories, it must be checked which basic memory technology (RDIMM / LRDIMM) is available.
- When using a multiprocessor system, the memory slots should always be configured identically for each CPU.
- Memory slots without a processor may not be used.
- If memory modules are provided with higher speeds than specified by the system, the memory speed is automatically adjusted to the system specifications.

### Information on memory installation

- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
  - Do not touch the gold pins of the memory module  $% \left( 1\right) =\left( 1\right) \left( 1\right) \left($
  - Only touch the sides of the memory module
  - Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.



### Further memory options for Supermicro SuperServer SYS-220HE-TNRD

8GB         SP473539         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           16GB         SP425208         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           32GB         SP425209         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           64GB         SP425210         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           64GB         SP425207         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP471052         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP425206         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP473538         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           256GB         SP471053         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®	Size	SKU	Technology	Туре	Number of pins	Brand	Reference no.
Registered)           32GB         SP425209         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           64GB         SP425210         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           64GB         SP425207         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP471052         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP425206         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP473538         DDR4         LRDIMM (ECC LR DIMM) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP471053         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®	8GB	SP473539	DDR4	,	288 Pin DIMM	PHS-memory®	
Registered)           64GB         SP425210         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           64GB         SP425207         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP471052         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP425206         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP473538         DDR4         LRDIMM (ECC LR DIMM) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP471053         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®	16GB	SP425208	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered)           64GB         SP425207         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP471052         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP425206         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP473538         DDR4         LRDIMM (ECC LR DIMM) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP471053         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®	32GB	SP425209	DDR4	,	288 Pin DIMM	PHS-memory®	
LR DIMM)  128GB SP471052 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory®  128GB SP425206 DDR4 LRDIMM (ECC LR DIMM)  128GB SP473538 DDR4 LRDIMM (ECC LR DIMM) PHS-memory®  256GB SP471053 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory®  RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory®	64GB	SP425210	DDR4	,	288 Pin DIMM	PHS-memory®	
Registered) 3DS  128GB SP425206 DDR4 LRDIMM (ECC LR DIMM) PHS-memory®  128GB SP473538 DDR4 LRDIMM (ECC LR DIMM) 3DS  256GB SP471053 DDR4 RDIMM (ECC Registered) 3DS  Registered) 3DS	64GB	SP425207	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM)  128GB SP473538 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory® LR DIMM) 3DS  256GB SP471053 DDR4 RDIMM (ECC 288 Pin DIMM PHS-memory® Registered) 3DS	128GB	SP471052	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM) 3DS  256GB SP471053 DDR4 RDIMM (ECC 288 Pin DIMM PHS-memory® Registered) 3DS	128GB	SP425206	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered) 3DS	128GB	SP473538	DDR4	•	288 Pin DIMM	PHS-memory®	
	256GB	SP471053	DDR4	,	288 Pin DIMM	PHS-memory®	
256GB SP471051 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory® LR DIMM) 3DS	256GB	SP471051	DDR4	LRDIMM (ECC LR DIMM) 3DS	288 Pin DIMM	PHS-memory®	

### PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.

For more information on warranty and service please visit https://www.phs-memory.com/-W5Y



### Contact Information

PHS-electronic gmbh - www.phs-memory.com -Karl-Götz-Str. 5 97424 Schweinfurt Germany Phone: +49 9721 784678 E-Mail: info@phs-memory.com Web: www.phs-memory.com

### Product Datasheet | SP473538 128GB Computer memory for SuperServer SYS-220HE-TNRD



All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at https://www.phs-memory.com